

PLANNING AND BUILDING DEPARTMENT

http://www.edcgov.us/Government/Building

PLACERVILLE OFFICE:

2850 Fairlane Court, Placerville, CA 95667

BUILDING

(530) 621-5315

bldgdept@edcgov.us

PLANNING (530) 621-5355 planning@edcgov.us LAKE TAHOE OFFICE: 924 B Emerald Bay Rd South Lake Tahoe, CA 96150 (530) 573-3330

bldgdept@edcgov.us

NON-RESIDENTIAL COOL ROOF FORM PERMIT APPLICATION FOR NON-RESIDENTIAL RE-ROOFS	ON (PART 9-C)	Permit #	
1. RE-ROOFS MUST MEET ENERGY CODE REQUIREMENTS FOR COOL ROOFS –See the Non-Residential Manual and \$110.8(i) of the 2016 California Energy Code.			
2. SOME EXEMPTIONS MAY APPLY. CHECK BOX IF APPLICABLE AND PROVIDE DOCUMENTATION			
The area of roofing replacement is less than 2,000 sq.ft., or less than 50% of the roof area, whichever is less			
The entire building has been analyzed under the Performance Approach			
The roof area is covered by building integrated photovoltaic panels			
Roof has a thermal mass over the roof membrane with a weight of at least 25 lb/ft ²			
3. IN ORDER TO MEET ENERGY CODE, ROOFING PRODUCTS MUST BE LISTED BY COOL ROOF RATING COUNCIL			
(CRRC) and must meet minimum values as shown:			
Low Slope roofs ($\leq 2:12$) Steep Slope roofs ($> 2:12$)			
Aged Solar reflectance0.63 OR SRI75 Aged Solar Reflectance			
Thermal Emittance0.75 Thermal Emittance0.75			
4. PROVIDE INFORMATION AS REQUESTED ON THE FOLLOWING:			
Roof Slope Product Type ²	Aged Solar	Thermal	
CRRC Product ID Number $1 \le 2:12 > 2:12$	Reflectance 3, 4	Emittance	SRI ⁵
1. The CRRC Product ID Number can be obtained from the Cool Roof Rating Council's Rated Product Directory at:			
www.coolroofs.org/products/search.php			
2. Indicate the type of product being used for the roof top (i.e. single-ply roof, asphalt roof, metal roof, etc.)			
3. If the Aged Reflectance is not available in the Cool Roof Rating Council's Rated Product Directory, then use the Initial			
Reflectance value from the same directory and use the equation (0.2 + 0.7 (ρ initial – 0.2) to obtain a calculated aged			
value, where ρ is the Initial Solar Reflectance.			
4. Check box if the Aged Reflectance is a calculated value using the equation			
5. SRI value may be calculated by using the SRI-Worksheet at http://www.energy.ca.gov/title24/ . Attach a copy.			
To apply Liquid Field Applied Coatings , the coating must be applied across the entire roof surface and meet the dry mil thickness or coverage			
recommended by the coatings manufacturer and meet minimum performance requirements listed in §118(i)4.			
Select the applicable coating:			
Aluminum-Pigmented Asphalt Roof Coating Cement-Based Roof Coating	Oth	er	
Documentation Author's Declaration Statement			
I certify that this Certificate of Compliance documentation is accurate and complete.			
Name: Signature:			
Company:	Date:		
Address:	If Applicable:		
1 Marcos.	CEA#		
	CEPE#		
City/State/Zip:	Phone:		